

be.tex® Samba Twin FR | Product no.: 4500-6266

Woven



PRODUCT FEATURES

Material: 100% polyester
Weight: 195 g/m²
Thickness: 250 µm
Stretch: < 1 %
Transmission factor: 38 %
Whitepoint: 94,1, -6 L*a*b

WIDTH
(cm)

ca. 500

LENGTH
(m)

ca. 50

APPLICATIONS

inflatables
display frame systems
light boxes
banners
booth construction

FEATURES

air tight
water tight
no fraying
good flatness
crease free
lotus effect
light diffusion coating

DESCRIPTION

Samba Twin is the solution in 500cm and complements the top seller Samba FR as a market standard for huge light boxes. Perfect backlighting characteristics and color-intensive print features. Absolutely crease free, therefore perfect for folded shipment, sun umbrellas, tents, blow-ups, beanbags, lightboxes, aluframes, etc. be.tex® Samba FR is even unlit and unprinted an absolute allrounder. Uncoated side with Lotus-effect.

NOTES

If prints are used in 500cm and 320cm side by side, we recommend using Samba Twin for both widths. Dye sub paper transfer on uncoated side: self-

The numbers above are purely guidelines and may differ depending on your personal printing needs and expectations. Since the printing results depend on numerous factors, we strongly advise to test your output in order to find out if any adjustments are necessary. A legally binding assurance of certain properties of the fabric can not be derived from the information above.

PRODUCTDATA

Digital

Last change: February 8, 2019



tests are recommended. For Latex prints with a very high ink-load (backlit) self-tests are recommended. Do not use self-adhesive products as flat profile 4545-1sk for processing (lotus on the back).

Technical textiles are naturally subject to weather conditions. This product can be used outdoor for a short term. When handled carefully this fabric can be even folded after printing.

The numbers above are purely guidelines and may differ depending on your personal printing needs and expectations. Since the printing results depend on numerous factors, we strongly advise to test your output in order to find out if any adjustments are necessary. A legally binding assurance of certain properties of the fabric can not be derived from the information above.